Improving Air Quality in Urban Areas by Enhancing Walking to School Programs: Addressing Mode Choice Barriers and Optimizing Walking Distance for Elementary School Students

Endang Widjajanti¹

Abstract

The purpose of this study is to determine the improvement in air quality that can occur if a walking-to-school program is implemented for elementary school students in the city of Depok. This research analyzes the transportation modes used by elementary school students to and from school in urban areas and the distance from their homes to school if they swalk. The study was conducted on students at SD Negeri Pasir Putih 03, Sawangan, Depok, to serve as a basis for programs aimed at encouraging students to walk to school. Data collection was carried out through field observations and interviews using a questionnaire via Google Forms, covering age, grade, address, departure and arrival times at school, modes of transportation used, and reasons for using them. Descriptive statistical methods were used to determine the walking distances of elementary school students by age. The most commonly chosen transportation mode for commuting to and from school was motorcycles (61.42%), followed by walking (29.96%). The rest used bicycles (2.80%) and a combination of walking and cycling. The analysis of walking distances for ages 6-13 showed that at the 50% cumulative percentage, the distance was less than or equal to 328 meters, with the shortest distance being 50 meters and the longest being 800 meters. Implementing a walking-to-school program for distances up to 100 meters is highly appropriate, as it not only improves students' health but also enhances air quality by reducing CO emissions during school hours. The estimated reduction in CO emissions with a moderate scenario during 1 hour in the morning along the distance between the gathering point and the school (100 meters) in Depok city is 431 grams/ day or equivalent to 87 kg/ year.

Keywords: Air Quality, Walking, Elementary School Students, Urban Areas, Walking Distance.

Introduction

Since every journey begins and ends on foot, all transportation users are pedestrians. In addition to its transportation function, walking is beneficial for health and can make a positive contribution to the environment, as it can reduce pollution produced by motor vehicles. Walking is considered an environmentally friendly and accessible method of transportation (Ananda et al, 2022). The distance that must be covered by walking is a very important factor in determining the choice of transportation mode for elementary school students. Often, students have to travel relatively long distances to reach school. Long distances can have a significant impact on the level of physical fatigue, time required for travel, and mental readiness of students (Makalev et al, 2023).

Walking is becoming less common due to the increasing use of motorized vehicles. People prefer to use cars/motorcycles due to cost, flexibility, convenience, travel time and weather protection (Gatersleben & Uzzell, 2007). Travel to school has also changed in recent years, with walking and cycling being replaced by motorized modes of transportation. School shuttles reduce physical activity and contribute to traffic congestion, especially during the morning rush hour (McDonald & Aalborg 2009; Carver et al. 2013a).

Conditions like the above also occur in Indonesia, especially in urban areas where research is needed to find out how the trends occur. In September 2023, the local government of Depok City launched a joint walking to school program to re-familiarize children to walk to school, which has been determined by a gathering point with a distance of 50 to 100 meters from the school (berita.depok.go.id, 2023) to automate the walking distance of elementary school students, This activity aims to get children used to walking, children are healthier and move a lot and are active in accordance with their growth and development. In addition, so

¹ Program Studi Magister Teknik Sipil Institut Sains dan Teknologi Nasional, Jl. Moch. Kahfi II, Bhumi Srengseng Indah, Kelurahan Jagakarsa – Jakarta Selatan 12620, Indonesia, Email: endangwidjajanti@istn.ac.id, (Corresponding Author)

that children can socialize with their friends. SD Negeri Pasir Putih 03, Sawangan, Depok was chosen because it is considered to represent the general condition of elementary schools in urban areas that can be accessed by students on foot.

The purpose of the study was to determine the improvement in air quality that occurs when a joint walking program to school is implemented by knowing the mode of transportation used by students to / from school and the proportion of students who go to / return from school on foot and the walking distance based on the age of the students of Pasir Putih 03 State Elementary School, Sawangan, Depok who walk from home to school and vice versa.

Overview

Walking to School as an Active Journey to School

Trips to school have undergone changes. Around three decades ago, most children commuted

to school on foot or by bicycle. However, in recent years, walking and cycling have been overtaken by motorized transport modes. Children (ren) being driven to school engenders inactivity and contributes to traffic congestion, especially in the AM peak hour (McDonald & Aalborg 2009; Carver et al. 2013a). To address the situation, ways to 'revive' active trips to school (ATS) are being analyzed (Buliung et al. 2011). The influences of different factors on school mode choice have been much studied (Bringolf-Isler et al. 2008; Larsen et al. 2009; Mitra et al. 2010). The impacts of trips to school on physical health have also been examined, with walking and cycling trips being the most common trips studied (Mitra & Buliung 2015; Stanley et al. 2015).

Walking as a mode of transportation offers various benefits, namely:

Environmental Aspects

Walking produces no direct emissions, thus contributing to the reduction of air pollution and greenhouse gas emissions.

Research by Andersen et al. (2015) estimated that replacing 5% of car trips with walking could reduce CO2 emissions by 5 million tons per year in Europe.

Health Aspects

The WHO recommends 150 minutes of moderate-intensity physical activity per week, which can be achieved through regular walking.

A study by Kelly et al. (2014) showed that regular walking can reduce the risk of cardiovascular disease, type 2 diabetes, and some cancers.

Economic Aspects

Walking does not require fuel costs or vehicle maintenance, so it can save individuals money.

Pedestrian infrastructure is generally cheaper than motorized infrastructure.

Social Aspects

Walking can increase social interaction and a sense of community in urban environments.

Pedestrian-friendly cities tend to have higher levels of safety and a better quality of life.

Air Pollution

Air pollution is one type of environmental pollution. Two causes of air pollution are:

Naturally such as dust blown by the wind, dust from volcanic eruptions, decaying garbage and others.

As a result of human actions, which can generally be divided into two parts, namely those from mobile sources (motorized vehicles, ships, etc.) and immobile sources, namely industrial activities.

The effects of air pollution on human health occur in the respiratory tract and organs of vision. Visually, air pollution can be seen from motor vehicle fumes (Abner, 2009). The most harmful pollutant to health is particulate matter, followed by NOx, SOx, hydrocarbons and carbon monoxide, which is the least toxic. In line with development in the industrial and transportation sectors, air pollution by combustion gases has also increased. The gas harmful to health is carbon monoxide (CO) gas, which is the combustion residue of carbon-containing fuels. One of the producers of CO gas in the air is motorized vehicles.

CO Emissions from Motorized Vehicles

The definition of Emissions according to Government Regulation Number 22 of 2021 is air pollutants resulting from human activities that enter and/or are introduced into the air. Emissions may or may not have the potential to become air pollutants."

Vehicle gas emissions are the residue of combustion in an internal combustion engine. This combustion residue will come out through the exhaust system or muffler. Harmful substances in vehicle gas emissions are:

CO (Carbon Monoxide), this gas has no color and no odor. However, this gas is very toxic when inhaled by humans. The most fatal result will result in fainting until death.

CO2 (Carbon Dioxide), this gas has a very dangerous impact because it greatly affects global warming.

NOX (Nitrogen Oxide), this gas can cause respiratory problems and is very painful to the eyes.

HC (Hydrocarbon), this gas comes from incomplete combustion in the car engine, so in this gas there are still remnants of gasoline vapor that are not burned and come out through the exhaust.

The three main factors that affect motor vehicle emissions on the road are the volume of motor vehicles, motor vehicle characteristics and traffic conditions (Ofrial et al., 2016). Motor vehicle carbon monoxide (CO) emissions in this study are influenced by the length of the road segment, the number of motor vehicles and vehicle emission factors. Emission factor is the mass of pollutants (grams) released by motor vehicles every kilometer traveled (Tarigan, 2009).

Vehicle Emission Load

Emission load is the mass of pollutants released into the air by traffic as a source of air pollution in a given unit of time (Sengkey, et al., 2010).

Calculation of emission load for a pollutant from motor vehicles on a road section using the following equation:

Where

E = CO gas emission on the road segment (gram/hr)

L = segment length

Ni = number of motor vehicles type i (kend/hr)

F = i Type i motor vehicle emission factor

The emission factor values used are vehicle exhaust emission factors for metropolitan cities and large cities in Indonesia, which are determined based on vehicle categories/types based on the Regulation of the Minister of Environment No. 12/2010 on the Implementation of Air Pollution Control in the Region. The emission factor values are presented in the following table.

Categories for air pollutant load calculation	СО
	g/km
Motorcycle	14
car (gasoline)	40
car (diesel)	2,8
car (other types of fuel)	32,4
Bus	11
Trucks	8,4

Table 2. Indonesia CO Emission Factor Values

Source: Minister of Environment Regulation No. 12 Year 2010

Overview of Depok City

Depok City is a city located in West Java Province, Indonesia. Depok City is part of the Jabodetabek metropolitan area and is located in the southern part of the Special Capital Region of Jakarta. Depok City was formed from the Depok Administrative City area with the addition of areas from Limo Subdistrict, Cimanggis Subdistrict, and Sawangan Subdistrict, as well as some villages from Bojonggede Subdistrict which were combined with Pancoran Mas Subdistrict.[4] The inauguration date of Depok City is designated as Depok City Anniversary. The population of Depok City based on data from the Ministry of Home Affairs of the Republic of Indonesia in mid-2023 was 1,927,867 people (Depok City in Figures, 2023).

Number of Schools and Students.	Elementary Schoo	ls (SD) by	v Subdistricts in De	nok City, 2021/2022
i tuinder of defidois and dradefito	, Dicilicintary beneo	(ob)	y cubalouleto in De	pon ony, 2021/ 2022

		School		Stidents (1/1000)			
Disrict	Public	Private	Total	Public	Private	Total	
Sawangan	21	19	40	8,418	3,152	11,57	
Bojongsari	14	20	34	7,306	3,483	10,789	
Pancoran Mas	24	30	54	13,834	8,898	22,732	
Cipayung	13	18	31	8,421	5,419	13,84	
Sukmajaya	31	24	55	15,065	6,478	21,543	
Cilodong	18	13	31	9,615	4,338	13,953	
Cimanggis	22	26	48	12,364	7,024	19,388	
Tapos	30	17	47	15,694	3,398	19,092	
Beji	18	14	32	8,727	3,492	12,219	

Volume: 3, No: 4, pp. 3542 – 3557										
ISSN: 2752-6798 (Print) ISSN 2752-6801 (Online)										
	https://ecohumanism.co.uk/joe/ecohumanism									
	-			DOI:	https://doi.org/10.6	<u>52754/joe.v3i4.387110.6</u> 2754				
Limo	9	15	24	5,075	3,588	8,663				
Cinere	7	10	17	3,174	2,771	5,945				
Depok City	Depok City 207 206 413 107,693 52,041 159,734									

Journal of Ecohumanism

2024

Source: Depok City Central Bureau of Statistics. 2023

Walking Program for Elementary School Students in Depok City

This program was launched in September 2023, where the Depok City Office of Women's Empowerment, Child Protection, Population Control and Family Planning (DP3AP2KB) launched a joint walking to school program to re-familiarize children to walk to school which has been determined at a gathering point with a distance of 50 to 100 meters from the school, the program in the local language is called Ngabring ka Sakola (Ngabaso) (berita.depok.go.id, 2023) This activity aims to get children used to walking, children are healthier and move a lot and are active according to their growth and development. In addition, children can socialize with their friends.

Research Methodology

The research methodology is presented in Figure 1.



Figure 1. Research Flow Chart

Research Location

The project location of Pasir Putih 03 State Elementary School, Sawangan, Depok is located on Jl. Raya Pasir Putih Sawangan, Depok city which is adjacent to a residential area, Depok City as part of the

Jabodetabek agglomeration (Jakarta-Bogor-Depok-Tangerang-Bekasi) is a city in the south that supports the capital city of DKI Jakarta, where some workers in DKI Jakarta reside in Depok City. (Figure 2)



Figure 2. Study Location

Source: Google maps, 2024

Data Collection

The collection technique used in this study was through questionnaires to obtain data on mileage and individual student characteristics such as age and grade level. Questionnaires, to obtain the necessary information for research purposes. The questionnaire will be carefully structured to cover various related variables, such as distance traveled on foot, travel time, as well as other factors that may affect student mobility.

The questions asked through the questionnaire included.

- Date of Birth
- Home Address
- Mode of travel to school (departure and return)
- Reason for mode use (optional)

The distance traveled by students was obtained from measurements on the distance map between the student's address and SDN Pasir Putih 03 Depok. The survey was conducted in October-November 2023.

Results And Discussion

The gender of the respondents was relatively balanced. By grade level, the largest was grade 6 (20%) and was almost evenly distributed with the smallest being grade 5 students (13.6%). The smallest student age was 6.8 years and the largest was 12.9 years. The gender and age distribution of respondents is presented in Table 3 and Table 4.

Table 3. Characteristics of Respondents Based on Class and Gender

	-			-		· · · · · · · · · · · · · · · · · · ·
Grade	Male	Female	Total	Grade	Male	Female
Class 1	33	47	80	Class 1	41%	59%
Class 2	42	47	89	Class 2	47%	53%
Class 3	30	35	65	Class 3	46%	54%
Class 4	45	23	68	Class 4	66%	34%
Grade 5	32	30	62	Grade 5	52%	48%
Grade 6	57	43	100	Grade 6	57%	43%
Total	239	225	464	Average	52%	48%

Source: Analysis Results, 2023

Table 4	Characteristics	of	Respondents	Based	on Age	(Vears)	•
Table 4.	Charactensucs	01	Respondents	Daseu	on Age ((Icais)	,

Age (years)	Number of Students s	Percentage
6.00-6.99	17	3,7%
7.00-7.99	76	16,4%
8.00-8.99	82	17,7%
9.00-9.99	73	15,7%
10.00-		
10.99	67	14,4%
11.00-		
11.99	77	16,6%
12.00-		
12.99	72	15,5%
Total	464	100,0%

Source: Analysis Results, 2023

Road Condition

Pavement condition in front of SDN Pasir Putih 03 (Jl. Pasir Putih) with a road width of 5 meters. Jalan Raya Pasir Putih, Sawangan, Depok has inadequate pedestrian facilities. Along the road starting from the front of Pasir Putih 03 State Elementary School to 100 meters from the elementary school there are no pedestrian facilities, only road shoulders for students to walk. The cross-sectional dimensions of the road are presented in the following figure.



Figure 3. Cross Section of Pasir Putih Road

Home to School Distance

The closest house to the school is 50 meters and the farthest is 22 km. The following figure shows that Pasir Putih 03 State Elementary School, Sawangan, Depok is located in a residential area up to a radius of 5 km-10 km. This shows the density of housing around the school.



Figure 4. Area Around the School

Source: Google earth, 2024

Mode of Transportation used by Students

The mode of transportation used to go to and from school by students of SDN 03 Pasir Putih Sawangam, Depok is the highest, with 61.42% of the total 464 students using motorcycles, while walking comes second (29.96%), the rest using bicycles 2.80% and a combination of walking and cycling. Only 1 student used a car (0.22%), a combination of walking with a bicycle 1.29%, walking with a motorcycle 2.80% and a bicycle with a motorcycle 1.51%. Here it can be seen that although the school area is a residential area that tends to be close, the number of students who walk to/from school is relatively not large, only 139 out of 644 students or around 30%. However, this figure is relatively high compared to the study conducted by Back L.F (2008) where the modes used by students to get to school are school buses (39.6%), walking (14.2%), and family cars (46.3%) and by Mac Donald N.C. (2007) where nationally in the United States from 1969 to 2001 there has been a decrease in the number of students walking from 40.7% to 12.9%. The mode of transportation to/from school of SDN 03 Pasir Putih Sawangan, Depok by age is presented in Table 5.

Age Range	Walking	Bicycling	Motor cycle	car	Combine		Total	%	
	1	2	3	4	1 & 2	1&3	2 & 3		
6.00-6.99	3	0	13	0	0	1	0	17	3,7%
7.00-7.99	21	1	52	0	0	2	0	76	16,4%
8.00-8.99	20	2	54	0	2	3	1	82	17,7%
9.00-9.99	27	3	38	0	1	2	2	73	15,7%
10.00-10.99	22	1	43	0	0	1	0	67	14,4%

Table 5. Modes	Used by	Students	to Get to	School by Age
----------------	---------	----------	-----------	---------------

Age Range	Walking	Bicycling	Motor cycle	car		Combine		Total	%
	1	2	3	4	1 & 2	1 & 3	2 & 3		
11.00-11.99	28	0	42	0	2	2	3	77	16,6%
12.00-12.99	18	6	43	1	1	2	1	72	15,5%
Total	139	13	285	1	6	13	7	464	100,0%
%	29,96%	2,80%	61,42%	0,22%	1,29%	2,80%	1,51%	100,00%	

Source: Analysis Results, 2024

The reason why parents choose the three main modes used by students, namely motorcycles, walking and bicycles is :

Motorcycle Mode

Of the 285 students who use motorcycles, 270 parents stated the reasons why they chose this mode, the most common being that the distance from home to school is far, besides that it is faster, safer and safer (because parents take them),

Walking

The reasons for students who walk, out of 139 students, 136 parents stated the reasons why they chose this mode, most (86%) stated because the distance from home to school is close, the rest are good for health (6%) and others (8%).

Bicycle

The biggest reason for choosing the bicycle mode is because they like it and because it is faster.









Figure 5. Reasons for choosing mode of transportation to/from school

Modes Used Based on Distance from Residence to School

The mode use based on the distance of residence to the school besides the private vehicle mode (because it was only done by 1 respondent) is presented in Table 4. From the table, it can be seen that the walking mode is chosen by students at a distance of 800 meters. If the distance from home to school is more than 800 meters, then students are more likely to be dropped off and picked up by motorcycle or a combination of walking with other modes of transportation, such as bicycle and motorcycle; The use of motorcycles does not correlate specifically with distance. As can be seen in Table 6, the use of motorcycle transportation is chosen by parents of students for both near and far distances.

Table 6. Use of	Transportation	Modes	Based of	n Distance	from	Residence to	o School

home to school distance (meters)	Walking (W)	Bicycle (B)	Motor cycle (MC)	W&B	W&MC	B&MC	Total
1-100	3	0	0	0	0	0	3
101-200	28	3	2	0	0	0	33
201-300	49	1	14	2	4	1	71
301-400	33	1	7	2	2	0	45
401-500	19	3	15	0	0	0	37
501-600	1	0	3	0	0	0	4
601-700	4	1	14	1	3	1	24
701-800	2	0	11	0	0	0	13
801-900	0	0	5	0	3	0	8

Journal of Ecohumanism 2024 Volume: 3, No: 4, pp. 3542 – 3557 ISSN: 2752-6798 (Print) | ISSN 2752-6801 (Online) https://ecohumanism.co.uk/joe/ecohumanism DOI: https://doi.org/10.62754/joe.v3i4.387110.62754

						,	
home to school distance (meters)	Walking (W)	Bicycle (B)	Motor cycle (MC)	W&B	W&MC	B&MC	Total
901-1000	0	0	30	1	1	0	32
1001-1100	0	0	12	0	0	1	13
1101-1200	0	0	7	0	0	0	7
1201-1300	0	2	19	0	0	0	21
1301-1400	0	0	6	0	0	0	6
1401-1500	0	0	5	0	0	0	5
1501-1600	0	0	4	0	0	0	4
1601-1700	0	0	15	0	0	0	15
1701-1800	0	1	20	0	0	0	21
1801-1900	0	0	10	0	0	1	11
1901-2000	0	0	3	0	0	0	3
2001-2100	0	1	10	0	0	0	11
2101-2200	0	0	8	0	0	0	8
2201-2300	0	0	8	0	0	2	10
2301-4400	0	0	46	0	0	1	47
>4400	0	0	11	0	0	0	11
Total	139	13	285	6	13	7	463

Source: Analysis Results, 2024

Walking Distance

The walking distance of students of SDN 03 Pasir Putih Sawangam Depok, measured based on the distance between school and residence (based on address) From the table, it can be seen that the mode of transportation to and from school on foot is chosen by students at a distance of 800 meters, and as many as 139 out of 463 students walk. The walking distance of students of SDN 03 Pasir Putih Sawangam Depok with the age range of 6-13 years old and the percentage of students who have a walking distance is presented in Figure 4. The walking distance that can be reached by 50% is 328 meters, with the shortest distance being 50 meters and the longest being 800 meters, the details of the calculation of walking distance are presented in the following table and figure.

Walking Distance and Percentage of Students Who Can Reach it

walking distance (m)	n	0⁄0	% of students who can reach
50	3	2%	100%
150	28	20%	98%
250	49	35%	78%
350	33	24%	42%
450	19	14%	19%
550	1	1%	5%
650	4	3%	4%
750	2	1%	1%
>800	0	0	
Total	139		

Source: Analysis Results, 2024

Table 8. Walking Distance of Students 03 Pasir Putih Sawangam Depok

Distance from l		center value x				
Range	Center Value	n	distance			
1-100	50	3	150			
101-200	150	28	4200			
201-300	250	49	12250			
301-400	350	33	11550			
401-500	450	19	8550			
501-600	550	1	550			
601-700	650	4	2600			
701-800	750	2	1500			
t	total	139	41350			
minimum	minimum distance (m)					
Maximum	Maximum distance (m)					
aver	rage (m)	297				

Source: Analysis Results, 2024



Walking Distance and Percentage of Students 03 Pasir Putih Sawangan Depok Who Are Able to Walk. Source: Analysis Results, 2024 Implementation of Walking to School Program (Ngabaso) at SDN Pasir Putih 03, Sawangan, Depok.

The implementation of Ngabaso activities that aim to familiarize children with walking at SDN Pasir Putih 03, Sawangan, Depok is proposed as follows:

- Location: 100 meters south of SDN 03 Pasir Putih Sawangan Depok
- Number of students participating : 644 students
- Number of students who switch modes of transportation: 643-139 = 504 motorcycles and 1 car (assuming gasoline fuel)
- Time to walk together: 6:45 a.m.



Figure 6 Location of The Starting Point of The Program Walking with Students of SDN Pasir Putih 03, Sawangan, Depok to School

Source: Analysis Results, 2024

With CO emissions by vehicle type during the arrival time to school (assumed to be 1 hour / 06.00-07.00), the total CO exposure that can be reduced is 0.75 g. Details of the calculation of reduced exposure to CO emissions on Pasir Putih road, at a distance of 100 meters south of SDN Pasir Putih 03, Sawangan, Depok are presented in Table 9,

Mode of Transportation	CO (g/km)	CO (g/m)	Number of vehicles at 100 meters	Reduced exposure to CO (g- 60 min)
139				
Motorcycle	14	0,014	504	0,71
Car (gasoline)	40	0,04	1	0,04
			Total	0,75

Table 9. Reduced Exposure to Co

Source: Analysis Results, 2024

Benefits of Walking to School (Ngabaso) Program Implementation in Depok City

The benefits of implementing the Walking to School Program (Ngabaso) in Depok City are known from the reduction in CO exposure due to students going to school using motorized transportation modes (motorcycles and private cars) with initial assumptions based on research results at SDN Pasir Putih 03, Sawangan, Depok, as follows.

The assumptions used are:

- Gathering point location: 100 meters away from the School premises
- Number of participating schools: moderate scenario i.e. 50% of elementary schools (public & private) per sub-district in Depok city (Table 1) and no increase in the number of schools throughout 2021-2023.
- Number of participating students: 50% of Primary Schools (Public & Private) based on the number of students per sub-district in Depok city.(Table 1) and no increase in the number of students throughout 2021-2023.
- Number of students who switch modes of transportation: Based on the proportion of study results aggregated in the following Table:

Table 10. Assumed Proportion of Transportation Modes to School Used by Primary School Students in Depok

	Walking	Walking Bicycling		car	Total		
%	30%	3%	62%	5%	100,00%		

- Observation time: 60 minutes (come to the gathering point 06.00-06.45, enter the school at 07.00)
- Number of school days in 1 year: 200

Based on the above assumptions, the calculation of the estimated CO exposure reduced by the walking program with elementary school students in Depok City at Pk. The estimated CO emissions due to motor vehicles used by elementary school students in Depok City at 06.00-07.00 at a distance of 100 meters from the school location that can be reduced because elementary school students walk to school together is 430,870 grams/day or 87 kg/year. With moderate assumptions, the Walking to School (Ngabaso) program in Depok City can be increased to an optimistic scenario (75% of schools participating) so that air quality improvements, especially CO reduction in Depok City, can be more significant.

Table 11: Reduced Co Exposure Due to The Walking Program with Depok City Elementary School Students at Pk.06.00-07.00

	No. of . School			Stude	ents (x1	(000	Mode of transportation (public & private) \				L	CO (gr)		
	Pu blic	Pri vate	Total	Pu bli c	Priv ate	Tota 1	Walki ng	bicy cle	Moto r- cycle	car	(met ers)	Motor- cycle	car	Total
Sawa				4,										
ngan				20	1,57	5,78					200			
-	11	10	20	9	6	5	1736	174	3587	289	0	10043	23140	33183
Bojon				3,										
gsari				65	1,74	5,39					170			
-	7	10	17	3	15	45	1728	162	3272	233	0	7786	15857	23644
Panco				6,										
ran				91	4,44	11,3					270			
Mas	12	15	27	7	9	66	3617	341	6909	499	0	26114	53906	80020

Journal of Ecohumanism
2024
Volume: 3, No: 4, pp. 3542 – 3557
ISSN: 2752-6798 (Print) ISSN 2752-6801 (Online)
https://ecohumanism.co.uk/joe/ecohumanism
DOI: https://doi.org/10.62754/joe.v3i4.387110.62754

										A		/		
Cipay				4.										
ung				21	2 70						155			
ung	7	0	16	05	2,70	6.02	2202	200	1206	204	155	0127	100/1	27060
	/	9	10	03	93	0,92	2202	208	4200	504	0	9127	10041	27909
Sukm				7,										
ajaya				53	3,23	10,7					275			
5.	16	12	28	25	9	715	3457	323	6528	463	0	25132	50958	76089
Cilod				4.										
ong				80	2.16	6.97					155			
ong	0	7	16	75	_,10	65	2227	200	1220	301	0	0178	18647	27824
C:	,	/	10	15	,	05	2231	207	422)	501	0	7170	10047	27024
Cima				6,										
nggis				18	3,51	9,69					240			
	11	13	24	2	2	4	3094	291	5887	423	0	19779	40596	60376
Tapos				7,										
•				84	1.69	9.54					235			
	15	9	24	7	9	6	3099	286	5762	399	0	18956	37490	56446
Beji				4.										
5				36	1.74	6.10					160			
	9	7	16	35	6	95	1964	183	3701	262	0	8289	16758	25047
Limo				2	-						-			
2				53	1 79	4 33					120			
	5	8	12	75	4	15	1376	130	2635	191	0	4426	9178	13604
Ciner				1.										
e				58	1 38	2 97								
C	4	5	0	7	1,50	2,97	020	80	1011	122	950	2155	4514	6660
	4	3	9	/	55	25	939	89	1811	155	850	2155	4514	0009
Deno				53										
Depo L				,8										
K				46	26,0	79,8	25449	239	4852	3496	206	140985	28988	43087
City	104	103	207	5	205	67	,225	6,01	4,79	,975	50	,8394	4,32	0,16

Conclusions

The implementation of the walking to school program at a distance of 100 meters to school is very appropriate in addition to improving student health and improving air quality during school hours. The estimated reduction in CO emissions under the moderate scenario for 1 hour in the morning along the distance between the gathering point and the school (100 meters) in Depok city is 431grams/day or equivalent to 87 kg/year.

References

- Ananda, N. D., Laswati, H., Rejeki, P. S., & Andri, S. (2022). Normal Walking Speed According to Age and Gender in Preliminary Students in Surabaya. Surabaya Physical Medicine and Rehabilitation Journal, Vol. 4 No. 1.
- Central Bureau of Statistics, (2023) "Depok City in Figures 2023" (pdf). depokkota.bps.go.id. pp. 43, 105. Archived from the original version on 2023-03-18.
- Bringolf-Isler B, Grize L, Mäder U, Ruch N, Sennhauser FH, Braun-Fahrländer C. 2008.
- Carver A, Timperio A, Crawford D. 2013a. Parental chauffeurs: what drives their transport choices? J Transp Geogr. 26:72-77.
- Carver A, Timperio A, Crawford D. 2013a. Parental chauffeurs: what drives their transport choices? J Transp Geogr. 26:72-77.
- Chillon, P., Penter, J., Corder, K., Jones, A. P., & Sluijs, E. (2015). A longitudinal study of the distance that young people walk to school. National Institutes of Health.
- Cooper. (2006). Business Research Methods. Jakarta: PT Media Global Edukasi.
- Gatersleben, B., & Uzzell, D. (2007). Affective Appraisals of the Daily Commute: Comparing Perceptions of Drivers, Cyclists, Walkers, and Users of Public Transport. Environment and Behavior, https://doi.org/10.1177/0013916506294032
- Hasan. (2004). Analyzing Research Data with Statistics. Jakarta: Bumi. Aksara.
- Kelly, P., et al. (2014). Systematic review and meta-analysis of reduction in all-cause mortality from walking and cycling and shape of dose response relationship. International Journal of Behavioral Nutrition and Physical Activity, 11(1), 132.Larsen K, Gilliland J, Hess P, Tucker P, Irwin J, He M. 2009. The influence of the physical environment and sociodemographic characteristics on children's mode of travel to and from school. Am J Public Health. 99:520-526.
 Lopez, C., Farina, Z., Gonzales, E., Cosic, M., Colmero, H., Casaubon, & Jesus. (2016). The Threshold Distance Associated
- With Walking From Home to School. Health education and behavior.
- Lythgo, N., Wilson, C., & Galea, M. (2011). Basic gait and symmetry measures for primary school-aged children and young adults. II: Walking at slow, free and fast speeds. Journal Gait & Posture.

- Makalew, F. P., Adisasmita, S. A., Wunas, S., & Aly, S. H. (2023). Influence of elementary students walking speed to children pedestrian pathway planning. Conference Series: Earth and Environmental Science.
- McDonald N, Aalborg A. 2009. Why parents drive children to school: implications for safe routes to school programs. J Am Plan Assoc. 75:331-342.
- McDonald N, Aalborg A. 2009. Why parents drive children to school: implications for safe routes to school programs. J Am Plan Assoc. 75:331-342.
- Mitra R, Buliung R, Roorda M. 2010. Built environment and school travel mode choice in Toronto, Canada. Transp Res Rec J Transp Res Board. 2156:150-159.
- Mitra R, Buliung R. 2015. Exploring differences in school travel mode choice behavior between children and youth. Transp Policy. 42:4–11.
- Noor. (2012). Research Methodology. Jakarta: Kencana Prenada Media.
- Nuryadi, Astuti, T. D., Utami, E. S., Budiantara, M. (2017). Basic Fundamentals of Research Statistics.
- Personal and environmental factors associated with active commuting to school in Switzerland. Prev Med (Baltim). 46:67-73.
- World Health Organization. (2021). WHO global air quality guidelines: particulate matter (PM2.5 and PM10), ozone, nitrogen dioxide, sulfur dioxide and carbon monoxide. Geneva: World Health Organization.